

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
22 January 2004 (22.01.2004)

PCT

(10) International Publication Number
WO 2004/008703 A1

- (51) International Patent Classification⁷: H04L 12/64, 12/44
- (21) International Application Number: PCT/EP2002/007699
- (22) International Filing Date: 10 July 2002 (10.07.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (71) Applicant (for all designated States except US): TELEFONAKTIEBOLAGET L. M. ERICSSON [SE/SE]; S-126 25 STOCKHOLM (SE).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): ANDERSSON, Jörgen [SE/SE]; Almarevägen 9, S-176 76 Järfälla (SE). FULLEMANN, John [SE/SE]; Fyrkantsvägen 4, S-163 46 Spanga (SE).
- (74) Agents: GRAY, Helen, Mary et al.; Albihns GmbH, Grasserstrasse 10, 80339 Munich (DE).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SYNCHRONOUS DATA TRANSFER SYSTEM FOR TIME-SENSITIVE DATA IN PACKET-SWITCHED NETWORKS



(57) Abstract: A transmission arrangement and method permits time-sensitive data to be transmitted through a packet-switched network and arrive synchronously at separate end points without synchronising all payload carrying nodes in the network. This is achieved by propagating a timing reference through the network from the sending node to the end nodes, each end node adjusting that phase of its local frequency generator to this timing reference. The sending node then sends data structure information to the end nodes, enabling the end nodes to regenerate the timing and structure of the synchronous data stream. Finally delay information is sent to each end node that allows the end nodes to adjust the start of synchronous data transmission by an amount such that all will commence transmission substantially simultaneously. With this information the end nodes independently recreate a signal in synchronisation. This solution has the advantage that the network infrastructure can remain substantially unchanged, although the timing sensitive application can treat the network as if it were a synchronised network.